

# HARDNER EMS-9



Screens treated with "HARDNER EMS-9(A·B)" resist water and solvent several times more than untreated screens.

## ■ How to apply

Mix the A and B parts together. Wet a developed screen with "HARDNEREMS-9(A·B)", dry under 40°C for 1 hour and wash with water, a then dry it again. Re-Cleaning of screens treated with "HARDNER EMS-9(A·B)" is difficult.

## ■ Remarks

Care should be exercised to avoid contact with skin or eyes.  
If accidentally spilled the affected area should be washed with water and mild soap.

## ■ Net

1Kgx2 (1set)

■ Please advise in freely.

■ SPEC We will revise & improve without informing

**MSJ MINOSHoji CO.,LTD.**  
SCREEN PRINTING MACHINE & MATERIAL  
<http://www.minoshoji.co.jp>

HEAD OFFICE / 648 Yakushi-cho Nijyo-agaru Nishinotoin Nakagyo-ku, Kyoto, JAPAN  
TOKYO OFFICE / 6-2-14 Honkomagome Bunkyo-ku, Tokyo, JAPAN  
OSAKA OFFICE / 3-3-10 Shinmachi Nishi-ku, Osaka, JAPAN  
UJI FACTORY / 58 Nakagawara Makishimacho Uji, Kyoto, JAPAN



TEL0081-75-211-4416 FAX0081-75-211-4497  
TEL0081-3-3947-0505 FAX0081-3-3947-0952  
TEL0081-6-6532-3855 FAX0081-6-6533-0030  
TEL0081-774-23-5333 FAX0081-774-24-1916



ISO9001/2000  
ISO14001/2004

12.2005