

MEDIA SCREEN TENSIONER



It is necessary for the correctness and beautiful image printing to make up the stencil which stretched more strong tension. By our original air cylinder, You can get more stronger and correctness tension.

- Air cylinder is heavy and the bigger for safety and stabilized stretching.
- We equipped the special clump system.
- You can get more stronger and the stabilized tension.
- By pulling out air, At the same time, The piston rod return to the original point. So, No need to use the hand.
- Max thickness 45mm, it can stretch the bigger frame size.
- It is strongly body to use it for a long time.
- It has equipped other 2 types which is 3S type for getting more high tension and up-down system for getting the stabilized tension.
- Specification : Screen tensioner M 1 pc

Model Code	Screen tensioner M
Clump width	Standard : 25cm Option : 15, 20, 30, 35cm
Cylinder stroke	Standard : 6cm Option : 10cm
Air supply	4~10kg/cm ²
Dimension	L450xH270xW (Standard) 250mm
Weight	6kg

- We prepare 12sets, 16sets, 20sets, 24sets and etc for your required screen frame.
12sets : Screen tensioner 12pcs, Duplication unit 1 pc, Air distribution 1 pc.

■ Please advise in freely.

■ SPEC We will revise & improve without informing

MINOSHOGI CO.,LTD.
SCREEN PRINTING MACHINE & MATERIAL
<http://www.minoshoji.co.jp>

HEAD OFFICE / 648 Yakushi-cho Nijyo-agaru Nishinotoin Nakagyo-ku, Kyoto, JAPAN
TOKYO OFFICE / 6-2-14 Honkomagome Bunkyo-ku, Tokyo, JAPAN
OSAKA OFFICE / 3-3-10 Shinmachi Nishi-ku, Osaka, JAPAN
UJI FACTORY / 58 Nakagawara Makishimacho Uji, Kyoto, JAPAN

SGIA

TEL0081-75-211-4416 FAX0081-75-211-4497
TEL0081-3-3947-0505 FAX0081-3-3947-0952
TEL0081-6-6532-3855 FAX0081-6-6533-0030
TEL0081-774-23-5333 FAX0081-774-24-1916



ISO9001/2000
ISO14001/2004

12.2005